



THE INFORMATION CONTAINED IN THIS DRAWING IS SOLE PROPERTY OF GLOBAL FLAG UNLIMITED. ANY REPRODUCTION IN PART OR IN WHOLE WITHOUT WRITTEN PERMISSION OF THE FLAG COMPANY, INC. IS PROHIBITED.

Global Flag Unlimited			
DRAWN RDW	10-19-06	Global Flag Unlimited	
Revised KBG	09/04/15	FLAGPOLE BEACON	
DESIGNER DOW	10-19-06	U.S. Patent #7,275,495	
APPROVED MWL	09/04/15	SIZE A	DWG NUMBER EXT-359
SCALE None	REV -	SHEET 1 OF 1	

Residential Beacons

Details

- Single light
- 110 Volt; LED bulbs
- 5" Gold or Silver ball
- 359 degree revolving truck
- Minimum 5' extra cable
- Rubber coated and direct buried wire

Installation Instructions

- Follow PVC ground sleeve instructions.
- Attach Beacon to top section of pole while threading cable through center of pole.
- Secure Beacon by tightening all three set-screws evenly.
- Continue threading cable through each section until you reach the last section.
- Connect cable to cable, matching the colors. (Always connect male to female.)
- Attach last sections together, pushing excess cable down into the bottom section.
- If you have an optional flash collar, slide it on now.
- Attach cleat with two screws provided.
- Thread rope halyard through truck and tie each snap into place using overhand knot.
- Stand pole up, following enclosed installation instructions.

Changing Bulbs

- Disconnect power from pole.
- Loosen retainer clips using phillips head screwdriver while holding bulb in place.
- Carefully remove bulb from socket (CAUTION: glass can break causing injury).
- Tighten retainer clips to secure bulb in its place.

UPDATED 9/23/2

Residential Series

The American Beacon Residential Series offers lighting options for External Halyard flagpoles in both Revolving and Stationary designs.

These options provide the most environmentally correct way for flagpole illumination, properly lighting the flag during nighttime hours without lighting adjoining properties and the night sky!

Style Truck

- 110 Volt System With Driver Contained Inside the Ball
- Can Be Converted to 12V for Solar Power Options
- Warm White, 3000K LED Light Rated for 25,000+ Hours
- 110V / 120V Input, 12 Volt Output
- Revolving Option - Wire Provided For Flagpole Height Plus 10' (Stationary Option Wire Length is 30')

Patent #7,273,493

*** - Specify Finish Option

SAT = Satin

BZT = BronzeTone Powder Coat

BLK = Black Powder Coat

WHT = White Powder Coat

Residential Revolving Beacon